



**SPECIFICATION:**

Polarity: LAMP  
 Dielectric Withstanding Voltage:  
 AC 1000V/60sec. r. m. s  
 Insulation Resistance:  
 1000M $\Omega$  Min at DC500V  
 Contact Resistance: 20m $\Omega$  Max  
 Durability: 100gf cycles Min  
 Terminal Retention Force: 2.27kgfper  
 Contact Min

**MATERIAL**

Contacts: Brass  
 Insulator : PBT UL 94V-0 Rate  
 Planted : Gold over  
 Planted : Gold over  
 Operating Temperature: -40° C to +105%  
 DC

未注公差 (TOLERANCE)		绘图 (DRAWN)	change	单位 (SCALE)	mm	料号 (PART NO.)	PH1800S (5)	奥海电子有限公司
X. $\pm 2^\circ$	X.			投影 (PROJECT)		图号 (DRAW NO.)		
.X $\pm 1^\circ$	.X $\pm 0.3$	校对 (CHECKED)		比例 (SCALE)		品名	2.54mm	
.XX $\pm 0.5^\circ$	.XX $\pm 0.2$	核准 (APPROVED)		版本 (EDITION)		(NAME)	Female Header	
.XXX	.XXX $\pm 0.1$		日期 (DATE)					