



ELECTRICAL CHARACTERISTICS:
CONTACT CURRENT RATING: 1 AMP.

DIELECTRIC WITHSTANDING VOL TAGE: AC 500V R.M.
INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT
DC 500V
CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM

特性: Specifications:
电学: Electrical:
接触电阻: Contact Resistance
30 milliohms MAX
耐电压: Dielectric Withstanding Voltage:
500 V AC 50 Sea level.
绝缘电阻: Insulation Resistance:
1000 MEGA ohms MIN
结构: Mechanical:
配合力: Mating Force:
4.0 磅 KAW 4.5 磅
插力: Inserting Force:
0.7 磅 MAX. 至少 0.7 磅
材料: Material:
壳体: Housing: High Temperature Thermoplastic.
UL 94V-0 耐高阻燃型
端子: Contact: Copper Alloy 铜合金
壳体: Shell: Copper Alloy 铜合金
电镀: Finish:
端子: Contact: Plated Gold in Mating Area;
Two Lead On Solder Lette
接触点镀金, 焊锡可焊
壳体: Shell:
Tin/Lead Plating 镀锡铅
Nickel Plating 镀镍

OWL ELECTRONICS LIMITED				成插图
品名	ST 3108PC	质	单位	罐
图号	HT0808	图纸编号	比例	1:1
制图	段向刚	审核	段向刚	日期 2004.02.23